



FlawSense


Surface flaw detection for
Wire, Cable, Tube, Hose, and Pipe




Detect slits, cracks, pits, bumps, blisters, lumps, scratches, neckdowns, streaks, wrinkles, and braid breaks in your production process




Lumps, Blisters



Braid Breaks, Wrinkles



Slits, Cracks




Pits, Scratches

FlawSense

Features and Benefits

- 360° orientation-independent flaw detection
- 360° orientation-independent OD and ovality measurement
- 100% non-contact, real-time inspection – inline or offline
- Up to 10,000 profiles per second for thorough coverage
- Automatic system setup
 - Press a button and let the system optimize for your product
 - Minimal operator interaction required
- Record detected flaws
 - 3D playback and visualization
 - Log information related to flaw length, height, and location







Total Vu HMI

Total Vu HMI software provides:

- User-configurable reporting with Microsoft Excel for traceability
- Access to data from anywhere in your facility with OPC UA
- Statistical process control (SPC) for insight into your process

Visualize detected flaws in 3D



Model	Minimum OD	Maximum OD	Minimum Detectable Defect Height
3-029	1 mm 0.040"	29 mm 1.14"	5 µm 0.0002"
3-069	3 mm 0.125"	69 mm 2.7"	25 µm 0.001"

